

# SAFETY DATA SHEET



**Superior**  
SEWING MACHINE & SUPPLY LLC

Issuing Date 01-Oct-2014

Revision Date 23-Apr-2015

Revision Number 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

### GHS product identifier

**Product Name** Textile Marking Texpen/Dalo -All colors

### Other means of identification

**Part Number** Black (13030, 23033, 23036), Orange (23103, 23106), Red (23023, 23026), White (13080, 23083, 23086), Yellow (13060, 23063, 23066)

**Formula Code** J2951 (Black), J3008 (Orange), J3006 (Red), J3038 (White), J3007 (Yellow)

**UN-Number** UN1263

**Synonyms** Textile and Fabric Texpen/Dalo Markers

### Recommended use of the chemical and restrictions on use

**Recommended Use** Solvent based marker

**Uses advised against** No information available

### Supplier's details

#### **Supplier Address**

Superior Sewing Machine & Supply LLC  
48 West 25th Street  
New York, NY 10010  
TEL: 1-800-274-5800

### Emergency telephone number

**Emergency Telephone Number** 800-535-5053 Infotrac

## 2. HAZARDS IDENTIFICATION


### Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

|   |            |
|---|------------|
| Serious Eye Damage/Eye Irritation                         | Category 2 |
| Skin Sensitization  | Category 1 |
| Carcinogenicity   | Category 2 |
| Specific Target Organ Systemic Toxicity (Single Exposure) | Category 3 |
| Flammable liquids   | Category 2 |

**GHS Label elements, including precautionary statements**

**Emergency Overview**

|  |  |   |
|--|--|---|
| <p><b>Signal Word</b><br/><b>Hazard Statements</b></p> <ul style="list-style-type: none"> <li>• May be harmful if swallowed</li> <li>• May be harmful in contact with skin</li> <li>• May be harmful if inhaled</li> <li>• Causes serious eye irritation</li> <li>• May cause an allergic skin reaction</li> <li>• Suspected of causing cancer</li> <li>• May cause drowsiness or dizziness</li> <li>• Highly flammable liquid and vapor.</li> </ul> | <p><b>Danger</b></p>  | <p><b>Appearance</b> Opaque, Varies, Thick viscosity,</p> <p><b>Physical State</b> Liquid.</p> <p><b>Odor</b> Pungent, Sweet, Mild,</p> |
|--|--|---|

**Precautionary Statements**

**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wash face, hands and any exposed skin thoroughly after handling.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing should not be allowed out of the workplace.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep cool.
- Wear protective gloves/protective clothing/eye protection/face protection.

**General Advice**

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

**Skin**

- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

**Inhalation**

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Ingestion**

- None

**Fire**

- In case of fire: Use CO2, dry chemical, or foam for extinction.

**Spills and Leaks**

- None

**Storage**

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

- Dispose of contents/container to an approved waste disposal plant.

**Hazard Not Otherwise Classified (HNOC)**

Not applicable

**Other information**

45.96832% of the mixture consists of ingredient(s) of unknown toxicity.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Synonyms**

Textile and Fabric Texpen/Dalo Markers

| Chemical Name                         | CAS-No     | Weight % | Trade secret |
|---------------------------------------|------------|----------|--------------|
| Titanium dioxide                      | 13463-67-7 | 10-30    | *            |
| Propylene glycol monomethyl ether     | 107-98-2   | 10-30    | *            |
| Cyclohexanone                         | 108-94-1   | 10-30    | *            |
| Acetone                               | 67-64-1    | 10-30    | *            |
| Cellulose, acetate                    | 9004-35-7  | 7-13     | *            |
| Carbon black                          | 1333-86-4  | 5-10     | *            |
| Bisphenol A - Epichlorohydrin polymer | 25068-38-6 | 1-5      | *            |

*\*The exact percentage (concentration) of composition has been withheld as a trade secret.*

**4. FIRST AID MEASURES**

**Description of necessary first-aid measures**

|                                   |   |
|-----------------------------------|---|
| <b>General Advice</b>             | Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.                          |
| <b>Eye Contact</b>                | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. |
| <b>Skin Contact</b>               | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.                    |
| <b>Inhalation</b>                 | Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.   |
| <b>Ingestion</b>                  | Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary               |
| <b>Protection of First-aiders</b> | Use personal protective equipment. Remove all sources of ignition.  |

**Most important symptoms/effects, acute and delayed**

**Most Important Symptoms/Effects** No information available.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to Physician** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical.

**Unsuitable Extinguishing Media** No information available.

**Specific Hazards Arising from the Chemical**

Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

**Explosion Data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Stop leak if you can do it without risk.

**Environmental Precautions**

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling** Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

**Incompatible Products** Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

| Chemical Name                                 | ACGIH TLV                                    | OSHA PEL  | NIOSH IDLH  |
|---|--|---|---|
| Titanium dioxide<br>13463-67-7                | TWA: 10 mg/m <sup>3</sup>                    | TWA: 15 mg/m <sup>3</sup> total dust<br>(vacated) TWA: 10 mg/m <sup>3</sup> total dust  | IDLH: 5000 mg/m <sup>3</sup>  |
| Acetone<br>67-64-1                            | STEL: 750 ppm<br>TWA: 500 ppm                | TWA: 1000 ppm<br>TWA: 2400 mg/m <sup>3</sup><br>(vacated) TWA: 750 ppm<br>(vacated) TWA: 1800 mg/m <sup>3</sup><br>(vacated) STEL: 2400 mg/m <sup>3</sup><br>The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors<br>(vacated) STEL: 1000 ppm | IDLH: 2500 ppm 10% LEL<br>TWA: 250 ppm<br>TWA: 590 mg/m <sup>3</sup>  |
| Propylene glycol monomethyl ether<br>107-98-2 | STEL: 150 ppm<br>TWA: 100 ppm                | (vacated) TWA: 100 ppm<br>(vacated) TWA: 360 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 540 mg/m <sup>3</sup>  | TWA: 100 ppm<br>TWA: 360 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 540 mg/m <sup>3</sup>  |
| Cyclohexanone<br>108-94-1                     | STEL: 50 ppm<br>TWA: 20 ppm<br>S*            | TWA: 50 ppm<br>TWA: 200 mg/m <sup>3</sup><br>(vacated) TWA: 25 ppm<br>(vacated) TWA: 100 mg/m <sup>3</sup><br>(vacated) S*  | IDLH: 700 ppm<br>TWA: 25 ppm<br>TWA: 100 mg/m <sup>3</sup>  |
| Carbon black<br>1333-86-4                     | TWA: 3.5 mg/m <sup>3</sup>                   | TWA: 3.5 mg/m <sup>3</sup><br>(vacated) TWA: 3.5 mg/m <sup>3</sup>  | IDLH: 1750 mg/m <sup>3</sup><br>TWA: 3.5 mg/m <sup>3</sup><br>TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |
| Silicon dioxide<br>7631-86-9                  | 10 mg/m <sup>3</sup>                         | 20 mppcf TWA; ((80)/(%) SiO2) mg/m <sup>3</sup>   | IDLH: 3000 mg/m <sup>3</sup><br>TWA: 6 mg/m <sup>3</sup>  |
| Aluminum hydroxide<br>21645-51-2              | TWA: 1 mg/m <sup>3</sup> respirable fraction | -   | -   |

*Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:*

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash goggles.

**Skin and Body Protection** Risk of contact: Chemical resistant gloves. Boots. Apron.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

|                       |                       |                       |                                 |
|-----------------------|-----------------------|-----------------------|---------------------------------|
| <b>Physical State</b> | Liquid                | <b>Appearance</b>     | Opaque, Varies Thick viscosity, |
| <b>Odor</b>           | Pungent, Sweet, Mild, | <b>Odor Threshold</b> | No information available        |

| <u>Property</u>                        | <u>Values</u>             | <u>Remarks/ - Method</u> |
|--|---------------------------|--------------------------|
| pH                                     | No data available         | None known               |
| Melting Point/Range                    | No data available         | None known               |
| Boiling Point/Boiling Range            | 55-157.78 °C / 131-316 °F | None known               |
| Flash Point                            | -0.56 °C / 31 °F          | None known               |
| Evaporation rate                       | > 1 (BuAc = 1)            | None known               |
| Flammability (solid, gas)              | No data available         | None known               |
| Flammability Limits in Air             |                           |                          |
| upper flammability limit               | No data available         |                          |
| lower flammability limit               | No data available         |                          |
| Vapor Pressure                         | No data available         | None known               |
| Vapor Density                          | > 1 (air = 1)             | None known               |
| Specific Gravity                       | > 1 @ 70°F                | None known               |
| Water Solubility                       | Negligible                | None known               |
| Solubility in other solvents           | No data available         | None known               |
| Partition coefficient: n-octanol/water | No data available         | None known               |
| Autoignition Temperature               | No data available         | None known               |
| Decomposition Temperature              | No data available         | None known               |
| Viscosity                              | No data available         | None known               |

**Flammable Properties** HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

**Explosive Properties** No data available  
**Oxidizing Properties** No data available

**Other information**

**VOC Content (%)** J2951 Black: 50%  
 J3006 Red: 46.9%  
 J3008 Orange: 39.74%  
 J3038 White: 39.74%  
 J3007 Yellow: 43.36%

**VOC (g/l)** J2951 Black: 488 g/L  
 J3006 Red: 466 g/L  
 J3008 Orange: 461 g/L  
 J3038 White: 465 g/L  
 J3007 Yellow: 485 g/L

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.



**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Heat, flames and sparks. Incompatible products.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

**Hazardous decomposition products**

Carbon oxides. Smoke Soot.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

**Inhalation** May be harmful if inhaled. May cause drowsiness and dizziness. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal

**Eye Contact** Irritating to eyes. Causes serious eye irritation.

**Skin Contact** May be harmful in contact with skin. May cause irritation.

**Ingestion** May be harmful if swallowed.

| Chemical Name                     | LD50 Oral             | LD50 Dermal              | LC50 Inhalation                                   |
|-----------------------------------|-----------------------|--------------------------|---|
| Titanium dioxide                  | > 10000 mg/kg ( Rat ) | -                        | -   |
| Propylene glycol monomethyl ether | = 5200 mg/kg ( Rat )  | = 13000 mg/kg ( Rabbit ) | > 24 mg/L ( Rat ) 1 h<br>= 54.6 mg/L ( Rat ) 4 h  |
| Cyclohexanone                     | = 800 mg/kg ( Rat )   | = 948 mg/kg ( Rabbit )   | = 10.7 mg/L ( Rat ) 4 h<br>= 8000 ppm ( Rat ) 4 h |
| Acetone                           | = 5800 mg/kg ( Rat )  | 1700mg/kg (rabbit)       | 18892 mg/m <sup>3</sup>                           |
| Carbon black                      | > 15400 mg/kg ( Rat ) | > 3 g/kg ( Rabbit )      | -   |
| Silicon dioxide                   | > 5000 mg/kg ( Rat )  | > 2000 mg/kg ( Rabbit )  | >2.2 mg/L ( Rat ) 4 h                             |
| Aluminum hydroxide                | > 5000 mg/kg ( Rat )  | -                        | -   |

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** No information available.

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Sensitization** May cause an allergic skin reaction.

**Mutagenic Effects** No information available.

**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

| Chemical Name    | ACGIH | IARC     | NTP | OSHA |
|------------------|-------|----------|-----|------|
| Titanium dioxide |       | Group 2B | -   | -    |
| Cyclohexanone    | A3    | Group 3  |     |      |
| Carbon black     | A3    | Group 2B | -   | X    |

**ACGIH: (American Conference of Governmental Industrial Hygienists)**  
A3 - Animal Carcinogen

**IARC: (International Agency for Research on Cancer)**  
 Group 2B - Possibly Carcinogenic to Humans  
 Group 3 - Not Classifiable as to its Carcinogenicity to Humans

**OSHA: (Occupational Safety & Health Administration)**  
 X - Present

**Reproductive Toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Chronic Toxicity** Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. May cause adverse liver effects.  
**Target Organ Effects** Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Lungs. Lymphatic system.  
**Aspiration Hazard** No information available.

**Numerical measures of toxicity - Product**

**Acute Toxicity** 45.96832% of the mixture consists of ingredient(s) of unknown toxicity.  
*The following values are calculated based on chapter 3.1 of the GHS document:*  
**LD50 Oral** 2271 mg/kg; Acute toxicity estimate  
**LD50 Dermal** 3214 mg/kg; Acute toxicity estimate  
**Inhalation dust/mist** 6.05 mg/L; Acute toxicity estimate mg/L

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

| Chemical Name                                 | Toxicity to Algae                                       | Toxicity to Fish  | Toxicity to Microorganisms  | Daphnia Magna (Water Flea)   |
|---|---|---|---|--|
| Acetone<br>67-64-1                            |   | LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus) | EC50 = 14500 mg/L 15 min  | EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna) |
| Propylene glycol monomethyl ether<br>107-98-2 |   | LC50 96 h: 4600-10000 mg/L static (Leuciscus idus) LC50 96 h: = 20.8 g/L static (Pimephales promelas)   |   | EC50 48 h: = 23300 mg/L (Daphnia magna)  |
| Cyclohexanone<br>108-94-1                     | EC50 96 h: = 20 mg/L (Chlorella vulgaris)               | LC50 96 h: 481-578 mg/L flow-through (Pimephales promelas) LC50 96 h: = 8.9 mg/L (Pimephales promelas)  | EC50 = 18.5 mg/L 5 min<br>EC50 = 21.3 mg/L 10 min<br>EC50 = 25 mg/L 5 min | EC50 24 h: = 800 mg/L (Daphnia magna)  |
| Carbon black<br>1333-86-4                     |   |   |   | EC50 24 h: > 5600 mg/L (Daphnia magna)   |
| Silicon dioxide<br>7631-86-9                  | EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata) | LC50 96 h: = 5000 mg/L static (Brachydanio rerio)   |   | EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)  |

**Persistence and Degradability** No information available.

**Bioaccumulation**

| Chemical Name                     | Log Pow |
|-----------------------------------|---------|
| Propylene glycol monomethyl ether | -0.437  |
| Cyclohexanone                     | 0.86    |
| Acetone                           | -0.24   |

**Other Adverse Effects**  
 No information available.



**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Methods** This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

**Contaminated Packaging** Do not re-use empty containers.

**US EPA Waste Number** D001  
U002  
U057

| Chemical Name            | RCRA | RCRA - Basis for Listing          | RCRA - D Series Wastes | RCRA - U Series Wastes |
|--------------------------|------|-----------------------------------|------------------------|------------------------|
| Cyclohexanone - 108-94-1 |      | Included in waste stream:<br>F039 |                        | U057                   |
| Acetone - 67-64-1        |      | Included in waste stream:<br>F039 |                        | U002                   |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste |
|---------------|----------------------------|
| Acetone       | Ignitable                  |

**14. TRANSPORT INFORMATION**

**DOT**

UN-Number UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II  
 Emergency Response Guide Number 128

**TDG**

UN-Number UN1263  
 Proper Shipping Name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**MEX**

UN-Number UN1263  
 Proper Shipping Name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**ICAO**

UN-Number UN1263  
 Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**IATA**

UN-Number UN1263  
 Proper Shipping Name Paint

**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Description** UN1263, Paint, 3, II

**IMDG/IMO**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**EmS No.** F-E, S-E  
**Description** UN1263, Paint, 3, II, (-0.56°C c.c.)

**RID**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification Code** F1  
**Description** UN1263, Paint, 3, II

**ADR**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification Code** F1  
**Tunnel Restriction Code** (D/E)  
**Description** UN1263, Paint, 3, II, (D/E)

**ADN**

**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification Code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II  
**Limited Quantity** 5 L  
**Ventilation** VE01

**15. REGULATORY INFORMATION**

**International Inventories**

**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**

|  |     |
|--|-----|
| <b>Acute Health Hazard</b>               | Yes |
| <b>Chronic Health Hazard</b>             | Yes |
| <b>Fire Hazard</b>                       | Yes |
| <b>Sudden Release of Pressure Hazard</b> | No  |
| <b>Reactive Hazard</b>                   | No  |

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ   |
|---------------|--------------------------|------------------------------------|--|
| Cyclohexanone | 5000 lb                  |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |
| Acetone       | 5000 lb                  |                                    | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

| Chemical Name    | CAS-No     | California Prop. 65 |
|------------------|------------|---------------------|
| Titanium dioxide | 13463-67-7 | Carcinogen          |
| Carbon black     | 1333-86-4  | Carcinogen          |

**U.S. State Right-to-Know Regulations**

"X" designates that the ingredients are listed on the state right to know list.

| Chemical Name                     | New Jersey | Massachusetts | Pennsylvania | Illinois | Rhode Island |
|-----------------------------------|------------|---------------|--------------|----------|--------------|
| Titanium dioxide                  |            | X             |              |          | X            |
| Acetone                           | X          | X             | X            |          | X            |
| Propylene glycol monomethyl ether | X          | X             | X            |          | X            |
| Cyclohexanone                     | X          | X             | X            | X        | X            |
| Carbon black                      | X          | X             | X            | X        | X            |
| Calcium resinate                  | X          |               |              |          |              |

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION**

|                    |                  |                |                   |                                 |
|--------------------|------------------|----------------|-------------------|---------------------------------|
| <b><u>NFPA</u></b> | Health Hazard 2  | Flammability 3 | Instability 0     | Physical and Chemical Hazards - |
| <b><u>HMIS</u></b> | Health Hazard 2* | Flammability 3 | Physical Hazard 0 | Personal Protection X           |

\*Indicates a chronic health hazard.

Prepared By Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

Issuing Date 01-Oct-2014  
Revision Date 23-Apr-2015  
Revision Note (M)SDS sections updated: 2.

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**