



SAFETY DATA SHEET

1. Identification

Product number 1000007592
 Product identifier **SILICONE SPRAY**
 Company information Sprayway, Inc.
 1005 S. Westgate Drive
 Addison, IL 60101 United States
 Company phone General Assistance 1-630-628-3000
 Emergency telephone US 1-866-836-8855
 Emergency telephone outside US 1-952-852-4646
 Version # 01
 Recommended use Lubricant
 Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
 Health hazards Skin corrosion/irritation Category 2
 Reproductive toxicity (fertility, the unborn child) Category 2
 Aspiration hazard Category 1
 Environmental hazards Not classified.
 OSHA defined hazards Not classified.

Label elements



Signal word Danger
 Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Suspected of damaging fertility. Suspected of damaging the unborn child.
 Precautionary statement
 Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
 Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Collect spillage.
 Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
 Hazard(s) not otherwise classified (HNOC) None known.
 Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	40 - 60

Chemical name	Common name and synonyms	CAS number	%
Solvent naphtha (petroleum), light aliph.		64742-89-8	20 - 40
n-Heptane		142-82-5	10 - 20
Cyclohexane		110-82-7	2.5 - 10
Naphtha (petroleum), Hydrotreated Heavy		64742-48-9	2.5 - 10
n-Hexane		110-54-3	0.1 - 1
Toluene		108-88-3	0.1 - 1
Other components below reportable levels			1 - 2.5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Dizziness. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Foam. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m ³
n-Heptane (CAS 142-82-5)	PEL	300 ppm
		2000 mg/m ³
n-Hexane (CAS 110-54-3)	PEL	500 ppm
		1800 mg/m ³
Propane (CAS 74-98-6)	PEL	500 ppm
		1800 mg/m ³
		1000 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

ACGIH

Components	Type	Value
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
n-Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3 300 ppm
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3 440 ppm
	TWA	350 mg/m3 85 ppm
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3 50 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection**Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection**Respiratory protection**

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Liquid.

Form

Aerosol.

Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.3 % estimated
Flammability limit - upper (%)	7.2 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	75 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.63 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dizziness. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 32880 mg/m ³ , 4 Hours > 5540 ppm, 4 Hours
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 5020 mg/m ³ , 4 Hours > 4980 mg/m ³ > 4980 mg/m ³ , 4 Hours > 4.96 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	4820 mg/kg
n-Heptane (CAS 142-82-5)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 29.29 mg/l, 4 Hours
n-Hexane (CAS 110-54-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 4 Hours > 5 ml/kg, 4 Hours
<i>Inhalation</i>		
LC50	Rat	> 5000 ppm, 24 Hours > 31.86 mg/l 73860 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	24 ml/kg 24 g/kg
	Wistar rat	49 g/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 1900 mg/kg, 24 Hours

Components	Species	Test Results
<i>Inhalation</i> LC50	Rat	> 5020 mg/m3, 4 Hours > 4980 mg/m3 > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	4820 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	Suspected of damaging the unborn child. Suspected of damaging fertility.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 23.03 - 42.07 mg/l, 96 hours
n-Heptane (CAS 142-82-5)		
Aquatic		
Fish	LC50	Mozambique tilapia (<i>Tilapia mossambica</i>) 375 mg/l, 96 hours

Components	Species	Test Results
n-Hexane (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 2.101 - 2.981 mg/l, 96 hours
Solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)		
Aquatic		
Algae	IC50	Algae 4700 mg/L, 72 Hours
Toluene (CAS 108-88-3)		
Aquatic		
Algae	IC50	Algae 433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 7.645 mg/L, 48 Hours
		Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (<i>Oncorhynchus kisutch</i>) 8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Cyclohexane	3.44
n-Heptane	4.66
n-Hexane	3.9
Propane	2.36
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Cyclohexane (CAS 110-82-7)	U056
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950
UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class	2.1
Subsidiary risk	-
Label(s)	2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

IMDG


UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

DOT

IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Cyclohexane (CAS 110-82-7)	Listed.
n-Hexane (CAS 110-54-3)	Listed.
Toluene (CAS 108-88-3)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cyclohexane	110-82-7	2.5 - 10
n-Hexane	110-54-3	0.1 - 1
Toluene	108-88-3	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)
 Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

From the library of: Superior Sewing Machine & Supply LLC

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexane (CAS 110-82-7)

n-Heptane (CAS 142-82-5)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Cyclohexane (CAS 110-82-7)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-17-2015

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.