



SAFETY DATA SHEET

SECTION 1 — IDENTIFICATION

Product identifier: AlbaChem® PSR
Product Number: 1062
Chemical Family: Mixture
Generic Description: Powdered Dry Cleaning Fluid
Date Revised: April 16, 2014

Manufacturer's name and address: Refer to supplier
Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300
(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This SDS complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

IMPORTANT: Read this SDS before handling and disposing of this product. Pass this information on to employees, customer, and users of this product.

SECTION 2 — HAZARDS IDENTIFICATION



DANGER

HAZARD CATEGORIES:

Flammable aerosol, category 1
Gas under pressure, dissolved
Specific Target Organ Toxicity – Single Exposure, category 3
Aspiration Hazard, category 1

HAZARD STATEMENTS:

Extremely Flammable Aerosol
Contains gas under pressure; may explode if heated
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways

Keep away from heat, open flames, and hot surfaces.-No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing spray. Use only outdoors or in a well-ventilated area.

Protect from sunlight. Store locked up. Store in a well-ventilated place. Do not expose to temperatures exceeding 122°F (50°C). Dispose of container to recyclables when completely emptied. KEEP OUT OF REACH OF CHILDREN.

IF SWALLOWED: Immediately call a poison control center or doctor. Do **NOT** induce vomiting. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

HMIS		PSR	
HEALTH	1	1=SLIGHT HAZARD; Irritation or minor reversible injury possible	
FLAMMABILITY	4	4=SEVERE HAZARD; Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air.	
PHYSICAL HAZARD	0	0=MINIMAL HAZARD; Materials that are normally stable under fire conditions and will not react to water, polymerize, decompose, condense, or self react.	
PERSONAL PROTECTION	A	A= Safety Glasses	

SECTION 3 — HAZARDOUS INGREDIENTS

COMPONENT(S)	CAS #	% by Weight
Pentane	109-66-0	45-55%
Methylal	109-87-5	<5%
Propane/n-Butane Blend	68476-86-8	25-35%

The chemical composition and percentages are considered trade secrets. Refer to Section 8 for exposure limits and recommendations.

SECTION 4 — FIRST AID MEASURES

Skin: For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eye: Immediately flush with plenty of water for at least 15 minutes, holding eyelids open at all times. Get medical attention immediately. **Inhalation:** Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist. **Ingestion:** If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Seek immediate medical attention. Do not give anything.

SECTION 5 — FIRE FIGHTING MEASURES

Extinguishing Media: Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools this may results in frothing and increase fire intensity. **Basic Fire Fighting Procedures:** Dangerous when exposed to heat or flame. This material can be ignited by flame or spark under normal atmospheric condition. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Pressurized Container: May explode when exposed to heat or flame. Empty containers may retain product residue including Flammable or Explosive vapors. DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers. **Dust Explosion Hazard:** None known. **Sensitivity To Mechanical Impact:** Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors. **Unusual Fire & Explosion Hazards:** During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water. **Fire Fighting Equipment/Instructions:** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Flash Point: concentrate: > -40.02F propellant: -156 F
Flammability limits in air:
 Concentrate: 7.8 upper % by volume 1.5 lower % by volume concentrate
 Propellant: 9.5 upper % by volume 1.8 lower % by volume propellant

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Emergency Action: Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate protective equipment and clothing during clean-up.

Containment: Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers.

SECTION 7 — HANDLING & STORAGE

FOR COMMERCIAL USE ONLY-NOT PACKAGED OR LABELED FOR HOME USE!

Handling: Keep this product away from heat, sparks or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing mists or aerosols of this product. Use this product with adequate ventilation. Do not reuse the empty container. **Storage:** Store in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition. Keep out of direct sunlight. Do not store above 120F (49 C).

Empty Container Precautions: Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. **Eye Protection:** Wear goggles or safety glasses with side shields. **Skin and Body Protection:** Impervious gloves should be used when handling this product. Use of protective coveralls and long sleeves is recommended. **Respiratory Protection:** Use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA). **General:** Use good hygiene practices in handling this material.

Exposure Limits: (PARTS PER MILLION)

Component(s)	TLV	OSHA-PEL	OSHA-STEL	SARA 313	Prop 65	VOC
Pentane	600 ppm	1000ppm	750ppm			X
Methylal	1000 ppm					X
Propane	1000 ppm					X
Butane	1000 ppm					X

Other raw material is considered trade secret.

SECTION 9 — PHYSICAL & CHEMICAL PROPERTIES

Appearance: White liquid

Odor: Hydrocarbon-like

Odor threshold: No data or not applicable

pH: No data or not applicable

Melting point/freezing point: No data or not applicable

Boiling point: No data or not applicable

Flash point: -156°F

Flammability: Flammable contents

Flame extension: No data or not applicable

Upper/lower explosive limits: LEL: 1.8 ; UEL 9.5

Vapor pressure: No data or not applicable

Vapor density: No data or not applicable

Relative density: 0.631

Evaporation rate: 28.6 (butyl acetate =1)

Solubility: No data or not applicable

Partition coefficient: No data or not applicable

Auto-ignition temperature: No data or not applicable

Decomposition temperature: No data or not applicable

Viscosity: No data or not applicable

VOC contents: 95.48%

SECTION 10 — STABILITY & REACTIVITY

Hazardous polymerization will not occur. Condition to avoid: Keep away from sources of ignition. Avoid contact with strong oxidizers, reducers, acids, and alkalis. Stability: This product is stable under normal conditions.

SECTION 11 — TOXICOLOGICAL INFORMATION

Pentane:	Oral LD50: >2g/kg (rat) Inhalation LC50: 364mg/l – 4 hours (rat)
Methylal:	Inhalation LC50: 15000ppm (rat) Oral LD50: 6653 mg/kg (rat)
Propane:	Inhalation LC50: 658 mg/L/4H (rat)
Butane:	Inhalation LC50: 658 mg/L/4H

SECTION 12 — ECOLOGICAL INFORMATION

No information available

SECTION 13 — DISPOSAL CONSIDERATION

We make no guarantee of warranty of any kind that the use of and/or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Waste Disposal: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

SECTION 14 — TRANSPORT INFORMATION

Ground Transportation: (Continental United States, Canada & Mexico): Consumer Commodity ORM-D

Ocean: UN 1950 Class 2.1 Flammable Gas, Limited Quantity

Air: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

SECTION 15 — REGULATORY INFORMATION

This product is not for use in VOC Regulated States. This includes: CA, DC, IL, NH, CT, DE, IN, MA, MD, ME, MI, NJ, NY, OH, PA, RI AND VA.

Pentane:	US. EPA CERCLA Hazardous Substances (40 CFR 302) SARA: Acute Health Fire Hazard	100lbs
Methylal:	Listed on TSCA Inventory. SARA: Acute Health Fire Hazard Reactive: Yes	
Propane:	TSCA Inventory	
Butane:	TSCA Inventory	

SECTION 16 — OTHER INFORMATION

The information in this MATERIAL SAFETY DATA SHEET is pursuant to 29 CFR 1910.1200 to convey information concerning the hazardous nature of this product. The information supplied was compiled from the most reliable sources available at the time of preparation and in light of the most reasonable foreseeable exposure situations expected from the intended use of this product. The material(s) may present greater or lesser hazard under other circumstances that are beyond the control of the manufacturer. Therefore it is imperative that all direction and warnings on the label be read and understood

Please refer to the first page of this SDS for appropriate revision dates. It is the user's responsibility to ensure that the SDS kept on file is the most up-to-date version of the SDS.