

SAFETY DATA SHEET

SECTION 1 / Identification

IDENTITY: PREMIUM BUFFING COMPOUND
PRODUCT CODE : FCBC25 - WHITE BUFFING COMPOUND BRICK

Product Use: Compound Buffing

Distributor: Superior Sewing Machine & Supply LLC
Address: 48 West 25th Street
New York, NY 10010
Telephone No: 212-691-5900
Emergency Telephone No: 315-797-0470
Date: 5/6/2015

SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.
Buffing operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

Signal Word:



Warning

Signal Word:

Warning

SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Hydrogenated Fatty Acids	57-11-4	less than 15%
Wax	N/A	less than 10%
Aluminum Oxides	1344-28-1	less than 75%

SECTION 4: First Aid Measures

Ingestion: If swallowed - seek medical attention
Inhalation: Move to a fresh air environment
Eye Contact: Flush thoroughly with water and call physician
Skin Contact: Remove dust from skin with warm water and soap

SECTION 5: Firefighting measures

Flash Point (method used): 350° F min (CoC)
LEL: N/A
Extinguishing Media: CO₂ Dry Chemical
Special Fire Fighting Instructions: Use Air Packs -Treat as Grease Fire
Unusual Fire and Explosion Hazards: Dense Smoke
Flammable Limits: No Data
UEL: N/A

SECTION 6: Accidental release measures

If material is spilled or released - Shovel and mop up. Normal clean up procedures per State and local laws. Care taken to avoid dust from becoming airborne.

SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in cool, dry area
 Protect from freezing temperatures
 No other precautions apply

SECTION 8: Exposure controls/personal protection

Hazardous Component	OSHA PEL	ACGIH / TLV
Hydrogenated Fatty Acids	15mg ./m ³	5mg ./m ³
Wax	N/A	N/A
Aluminum Oxides	15mg ./m ³	5mg ./m ³

Special: None

Mechanical (General): To maintain employee below permissible limits.

Ventilation: Local Exhaust / Fan or Open Window

Respiratory Protection: OSHA/MOHA approved dust mask / respirator

Gloves: Yes

Eye Protection: Safety Glasses

Other: Long sleeve protective clothing

SECTION 9: Physical and chemical properties

Boiling Point: > 450°F		Specific Gravity: 1.5 to 3.5
Vapor Pressure (mm Hg): N/A		Melting Point: 140°F
Vapor Density: N/A		Evaporation Rate: N/A
Solubility in Water: Insoluble		(Butyl Acetate=1)
Appearance & Odor: Tube form - white		

SECTION 10: Stability and Reactivity

Stability: Yes
Incompatibility: N/A
Hazardous Decomposition of By-Products: N/A
Hazardous Polymerization: Will not occur
Conditions to Avoid: N/A

SECTION 11: Toxicological Information

Route(s) of Entry :	Inhalation: <u> No </u>	Skin: <u> Yes </u>	Ingestion: <u> Yes </u>
Health Hazards (Acute & Chronic - Buffing operations may cause lint and abrasives to become airborne			
We recommend respirator and ventilation.			

Effects of overexposure: Irritation to eyes, ears, nose and throat	
Carcinogenicity: N/A	NTP: N/A
IARC Monographs: No	OSHA Regulated: No

SECTION 12: Ecological information (Non-Mandatory)

Ecotoxicity: none

SECTION 13: Disposal considerations (Non-Mandatory)

Per State and Local Law

SECTION 14: Transport Information (Non-Mandatory)

Not regulated as dangerous goods

SECTION 15: Regulatory Information (Non-Mandatory)

None

SECTION 16: Other Information (Non-Mandatory)

Revision Date: 05/06/2015

Revision Summary:

Update all sections - GHS / SDS compliance

Revised By: A.Battle