



# MATERIAL SAFETY DATA SHEET

From the library of: Superior Sewing Machine & Supply LLC

## 1. Product and Company Identification

**Product number** 961-004  
**Product name** Hoil Penetrating Oil & Rust Preventative  
**Effective date** 01-Mar-2011  
**Company information** Sprayway, Inc.  
 484 Vista Ave.  
 Addison, IL 60101 United States  
**Company phone** General Assistance 630-543-7600  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Version #** 10  
**Supersedes date** 18-Aug-2010

## 2. Hazards Identification

**Emergency overview** Aerosol. FLAMMABLE  
 CONTENTS UNDER PRESSURE.  
 Will be easily ignited by heat, spark or flames. Contact with this material can cause irritation to the skin, eyes and mucous membranes. May be harmful if absorbed through skin. Prolonged exposure may cause chronic effects.

**Potential health effects**

**Routes of exposure** Eye contact. Skin contact. Ingestion.

**Eyes** Contact may irritate or burn eyes. Health injuries are not known or expected under normal use.

**Skin** May be harmful if absorbed through skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Inhalation of aerosol may cause irritation to the upper respiratory tract. Prolonged inhalation may be harmful.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Risk of serious damage to the lungs (by aspiration). Components of the product may be absorbed into the body by ingestion.

**Target organs** Kidneys.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

**Chronic effects** Blood. Central nervous system. Liver. Lungs.  
 Unconsciousness. Cyanosis (blue tissue condition, nails, lips, and/or skin). May be harmful if absorbed through skin. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. None known. May cause delayed lung injury.

**Signs and symptoms** Discomfort in the chest. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin). Coughing. Liver enlargement. Jaundice.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	50 - 60
Propane	74-98-6	8 - 10
2-Butoxyethanol	111-76-2	8 - 10
Non-hazardous and other components below reportable levels		20 - 40

## 4. First Aid Measures

### First aid procedures

<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Immediately flush skin with plenty of water. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
<b>Inhalation</b>	Move to fresh air. Get medical attention if symptoms persist.
<b>Ingestion</b>	Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

**Notes to physician** Symptoms may be delayed.

## 5. Fire Fighting Measures

<b>Flammable properties</b>	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Water. Water spray. Water fog. Alcohol foam. Dry chemical. Carbon dioxide (CO <sub>2</sub> ).
<b>Protection of firefighters</b>	
<b>Specific hazards arising from the chemical</b>	Fire may produce irritating, corrosive and/or toxic gases.
<b>Protective equipment and precautions for firefighters</b>	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out.

## 6. Accidental Release Measures

<b>Methods for containment</b>	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift.
<b>Methods for cleaning up</b>	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

## 7. Handling and Storage

<b>Handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with skin. Avoid prolonged exposure.
<b>Storage</b>	Store locked up. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

## 8. Exposure Controls / Personal Protection

### Exposure limits

#### ACGIH

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established

**OSHA**

Components	CAS #	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established

**Personal protective equipment****Skin protection**

Wear appropriate chemical resistant clothing. Wear chemical protective equipment that is specifically recommended by the manufacturer.

**Respiratory protection**

Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

## 9. Physical & Chemical Properties

<b>Appearance</b>	Compressed liquefied gas.
<b>Boiling point</b>	332.6 °F (167.2 °C) estimated
<b>Color</b>	Dark brown.
<b>Density</b>	0.7875 g/cm <sup>3</sup> estimated
<b>Flammability (HOC)</b>	37.9966 kJ/g estimated
<b>Flash back</b>	Yes
<b>Flash point</b>	-156 °F (-104.4 °C) Propellant
<b>Form</b>	Aerosol.
<b>Freezing point</b>	Not available
<b>Odor</b>	odourless
<b>pH</b>	Not applicable
<b>Physical state</b>	Liquid.
<b>Pressure</b>	38 - 48 psig @70F
<b>Solubility</b>	Negligible
<b>Specific gravity</b>	0.7876 estimated

## 10. Chemical Stability & Reactivity Information

<b>Chemical stability</b>	Risk of ignition.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological Information

**Acute effects** Acute LD50: 1387 mg/kg estimated, Rat, Dermal

**Component analysis - LD50****Toxicology Data - Selected LD50s and LC50s**

2-Butoxyethanol	111-76-2	Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat 470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

**Sensitization** Not expected to be hazardous by OSHA criteria.

**Teratogenicity** Not expected to be hazardous by OSHA criteria.

## 12. Ecological Information

**Ecotoxicity** Components of this product have been identified as having potential environmental concerns.

LC50 78.96 mg/L, Fish, 96.00 Hours,  
EC50 7019 mg/L, Daphnia, 48.00 Hours,  
The product itself has not been tested.

## 13. Disposal Considerations

**Waste codes** D001: Waste Flammable material with a flash point <140 F

**Disposal instructions**

Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

**14. Transport Information**

**Department of Transportation (DOT) Requirements**

**Basic shipping requirements:**

<b>Proper shipping name</b>	Consumer commodity
<b>Hazard class</b>	ORM-D
<b>Subsidiary hazard class</b>	None
<b>Additional information:</b>	
<b>Packaging exceptions</b>	156, 306
<b>Packaging non bulk</b>	156, 306
<b>Packaging bulk</b>	None

**IMDG**

**Basic shipping requirements:**

<b>Proper shipping name</b>	AEROSOLS
<b>Hazard class</b>	2.1
<b>UN number</b>	1950
<b>Additional information:</b>	
<b>Packaging exceptions</b>	LTD QTY
<b>Item</b>	5F
<b>Labels required</b>	None
<b>Transport Category</b>	2



**IATA**

**Basic shipping requirements:**

<b>Proper shipping name</b>	Aerosols, flammable
<b>Hazard class</b>	2.1
<b>UN number</b>	1950
<b>Additional information:</b>	
<b>Packaging exceptions</b>	LTD QTY
<b>Labels required</b>	2.1



**15. Regulatory Information**

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
 CERCLA/SARA Hazardous Substances - Not applicable.

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

2-Butoxyethanol	111-76-2	1.0 % de minimis concentration (applies to R-(OCH <sub>2</sub> CH <sub>2</sub> ) <sub>n</sub> -OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)
-----------------	----------	--

**Occupational Safety and Health Administration (OSHA)**

<b>29 CFR 1910.1200 hazardous chemical</b>	Yes
--	-----

**CERCLA (Superfund) reportable quantity**

None

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Section 302 extremely hazardous substance</b>	No
<b>Section 311 hazardous chemical</b>	Yes

**Hazard categories (311/312)** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations**

**U.S. - Pennsylvania - RTK (Right to Know) List**

2-Butoxyethanol	111-76-2	Present
Propane	74-98-6	Present
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Present

**16. Other Information**

<b>Further information</b>	HMIS® is a registered trade and service mark of the NPCA.
<b>HMIS® ratings</b>	Health: 1* Flammability: 4 Physical hazard: 0
<b>Disclaimer</b>	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.
<b>MSDS sections updated</b>	Product and Company Identification: Product and Company Identification Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Physical & Chemical Properties
<b>Prepared by</b>	Regulatory Compliance

From the library of: Superior Sewing Machine & Supply LLC